



MANAGED LANES

Implementation Plan



MLIP / OPS Update

Stakeholder Meeting #4

June 3, 2015





Agenda

- OPS Overview
 - Recommendations
- MLIP Overview
 - Managed Lane Strategies
 - Operational Analysis
 - Assumptions to Inform Financial Analysis
 - Results of Financial Analysis
- Next Steps












OPS Overview





Objectives

- Identify bottleneck areas
- Identify and evaluate potential low-cost improvements
- Quick implementation – 6 months to 5 years
- Document a prioritized list of operational projects











Identified Bottlenecks








Previously Identified Bottlenecks







Recommended Projects








Recommended Projects by Cost Range

 74 projects totaling approximately \$181 M







Atlanta Regional MANAGED LANES


Implementation Plan

MLIP Overview





Managed Lane Corridors Currently in Operation or Under Development







Planning Assumptions

- All new limited access capacity in Metro Atlanta will likely be tolled
- Eliminate assumptions of long-term concession agreements
- Evaluate lower-cost managed lane treatments
- Accommodate regional transit
- Project level assumptions based on Plan2040 (Sept 2012)





Implementation Plan



Transit Considerations

- Transit will be able to use inside (left) tolled lanes for free
- Park-and-ride lots considered in the development of access points
- GRTA bus drivers provided input on bottleneck locations and potential solutions for MLIP/OPS
- Ramp meter bypass lanes for transit recommended as part of OPS





Managed Lane *Implementation* Plan (MLIP)

- Updating MLSP as part of Managed Lanes <u>Implementation</u> Plan (MLIP) to:
 - Build upon previous MLSP goals
 - Reflected funding constraints
 - Identify feasible locations for managed lane projects
- Incorporate recommendations into RTP and TIP update, as appropriate







Atlanta Regional MANAGED LANES Implementation Plan

Managed Lane Strategies



Implementation Plan



Managed Lane Strategies

- Consider traditional priced managed lane solutions
 - New Lanes
- Consider non-traditional priced managed lane solutions
 - Dynamic Flex Lanes utilizing shoulders
 - Reversible Lanes using Moveable Barriers
- Intent is to not "reduce" current travel options for motorists





Managed Lane Strategies


NEW LANES







New Lane – Typical Section BEFORE










New Lane – Typical Section AFTER









New Lanes Characteristics

- Configurations
 - 1-Lane in each direction
 - Maintain/reduced existing lane widths to 11' and construct a new outside lane that is 12'
 - Separation through delineators and pavement stripings
 - Access type and locations
 - Direct access ramps connecting to surrounding arterial system
 - Slip ramp access to adjacent general purpose lanes
 - Potential for system-to-system interchange
- Operations/Analysis Periods
 - Both directions
 - 24/7 operations







Managed Lane Strategies


Dynamic Flex Lanes







Dynamic Flex Lanes – Typical Section BEFORE










Dynamic Flex Lanes – Typical Section AFTER










ATMS Signage – Off-Peak










Dynamic Flex Lane Characteristics

- Configurations
 - 1-Lane in each direction
 - Maintained existing lane widths and rebuilt outside shoulder to a new 12' lane (for use during peak periods only) and 2' outside shoulder
 - Separation through pavement stripings
 - Access type and locations
 - Slip ramp access to adjacent general purpose lanes spaced every 2-3 miles
- Operations/Analysis Periods
 - Both directions
 - Peak period operations





Corridor Strategies Initially Evaluated







Atlanta Regional MANAGED LANES Implementation Plan

Corridor Strategy Prioritization





Prioritization Structure Evaluation Criteria











TRANSPORTATION MOBILITY

Vehicle and Person Throughput

Changes in travel speeds or travel time savings

Reduction of vehicle delay

Facilitation of transit options

FINANCIAL FEASIBILITY

Revenue/mile Cost/mile Project financing index

SYSTEM CONNECTIVITY & ECONOMIC GROWTH

Managed lane system connectivity

Connectivity to major employment centers

Jobs accessed within 45 minutes of travel by car or transit

SYSTEM PRESERVATION & ENVIRONMENTAL SUSTAINABILITY

System preservation

Level of
environmental impacts
Flexible lane
management

PROJECT SUPPORT & READINESS

Project readiness

General constructability
and schedule








MLIP Prioritization Structure - Weighting Scenario Analysis


MLIP Project Prioritization Theme Weighting Scenario
Stakeholder/CID Average







Identified Corridor Strategies







Atlanta Regional MANAGED LANES Implementation Plan


Operational Analysis

System-to-System Access & Corridor Performance






Option 1: System-to-System Interchange Costs







Option 2: Lower Cost Operational Improvements







Weaving Analysis – Potential Improvements

- Weaving analysis resulted in increased capital cost of \$15.3M
- OPS projects necessary to achieve acceptable LOS
 - #15 Extend flex lane to I-285E Exit with signing and striping modifications (I-20E WB project, \$2.08M)
 - #18.1 Extend flex lane to I-20 WB Exit (I-20W WB project, \$3.87M)
 - #18.2 Extend flex lane to new exit to I-285 (I-20W EB project, \$7.72M)
 - #32.2 Extend flex lane to I-85 exit with signing and striping modifications (I-285E NB project, \$0.46M)
- Additional operational strategies necessary:
 - I-75S NB Extend flex lane to SR 54 Exit with signing and striping modifications (\$0.25M)
 - I-20E EB Extend flex lane to SR 162 Exit with signing, striping and widening modifications (\$0.91M)







Corridor Performance – No Build Assumptions


- No-Build Assumptions includes Managed Lanes on
 - HOV Inside I-285 (Existing)
 - 1 HOV lane in each direction where currently existing
 - I-75/I-575 NWC
 - 2/1 reversible ETL
 - I-75 South from SR 138 to SR 155
 - 2 reversible ETL
 - I-85 North from I-285 to Old Peachtree Rd
 - 1 HOT3+ in each direction
 - I-285 Top End
 - 2 ETL in each direction








Corridor Performance – Changes in Speeds & Delay for New Lanes and Dynamic Flex Lanes



2040 Total Vehicle Delay During AM & PM Periods (Hours)





Note: Build results include managed lane solutions along all study corridors.






Atlanta Regional MANAGED LANES Implementation Plan

Assumptions to Inform Financial Analysis





Packages for Financial Analysis







Development of Traffic and Revenue

- Willingness-to-pay
 - GDOT's 2007/2010 stated preference survey
 - Mean value of time range \$7 \$15 per hour

Policies

- Set toll rates to maximize performance (maintain ~45 mph in managed lane)
 - Therefore, traffic remains fairly consistent in the managed lanes between 2020 and 2040 while the demand for the lane increases over time
- ETL (except for I-85 N, which was assumed to remain HOT3+)
- All transit was allowed for free; however, no changes were made to routes or headways

Revenue Forecasts

- 2020-2040 revenue interpolated using 2020 and 2040 model results
- Beyond 2040, 50% revenue growth rate was assumed
- Ramp-up factors
 - Year 1 (65%); Year 2 (80%); Year 3 (90%); Year 4 (95%)







Development of Capital Costs – Roadway

- Roadway Items
 - Grading Complete
 - Clearing & Grubbing
 - PCC Widening
 - Asphalt Widening
 - Asphalt Mill/Overlay
 - Pavement Demo
 - Concrete Barrier (Type 2)
 - Concrete Median
 - Sidewalk
 - Concrete Curb and Gutter
 - ROW
 - ROW Take
 - Guard Rail

- Structural Items
 - New Bridge
 - Bridge Removal
 - Bridge Widening
 - Retaining Walls
 - Soundwalls
- Drainage Items
 - Drainage Structures
 - Drainage Pipe
 - Paved Ditched/Flume
 - Rip Rap
- Traffic Items
 - Signal Timing adjustments
 - New Intersection Signal
 - Traffic Cameras

- Signing and Marking Items
 - Striping
 - Overhead Signs
 - Remove Overhead Signs
 - Retrofit Overhead Signs
 - Roadside Signs
 - Changeable WarningSigns
 - Remove Exist Solid Traffic Stripe
 - Remove Traffic Markings
 - Light Poles (Tolling Safety)
 - Light Poles (Large Mast)
 - Fiber Optic Line
- Erosion Control (+ MS4)
- Traffic Control







Development of Capital Costs – Tolling

- Lane Equipment
- OCR Development and License Fee
- Mobilization
- System Integrator design, PM, testing and documentation
- Installation
- System Testing and Oversight

- Toll Host/Plaza Server
- Lane Software
- Generators
- ITS Equipment
- Testing







Development of O&M Costs – Roadway

- HERO Maintenance Vehicle
- HERO Operators
- HERO Vehicles
- Asphalt Mill/Overlay
- Changeable Message Signs
- Changeable Message Sign Replacement
- Emergency Towing
- Snow & Ice Removal
- Special Events/Emergency Closures







Development of O&M Costs – Tolling

- Tolling
 - Lane Equipment
 - Back Office Hosting Maintenance
 - ETC Lane Equipment Maintenance,
 Hosting, Software Maintenance
 - ITS Equipment
 - Generators
 - Toll Admin and Overhead
 - Annual Utilities
 - NaviGAtor Upgrade Maintenance
 - SRTA Integration Maintenance
 - WAN Access
 - R&R Capital Replacements

- Customer Service Center Costs
 - Electronic Toll Collection
 Processing Fee (per transaction)
 - Credit Card Fees
 - Image Review Costs
 - DMV Lookup Costs
 - Violation Notice Costs
 - Collection Costs







Project Delivery Spectrum

Traditional Public

Public-Private-Partnership

Design Bid Design Build Finance Operate Maintain (DBFOM)

(DBB)

Design Build Finance Operate Maintain (DBFOM)

- Availability - Concession Payment

- Typically for gap financing or cashflow management
- Construction term loans are common
- Final term can vary
- Financing amount (% of construction cost) can vary
- Desired output (one page summaries, narratives explaining structures, etc.)








Input Assumptions for Packages

DBF Structure




Assumptions

- Upfront Costs 45% or 70%
 - Milestone Payments
 - Substantial Completion Payments
- DBF Finance 55% or 30%
- DBF Payback 10 year or 20 year
- Debt Rate 4.5%



Toll Backed Bonds Structure



Financial Levers

- Toll Revenue Bonds
- TIFIA
- Private Activity Bonds (PAB)
- Coverage
- Borrowing Rate
- Debt-to Equity Ratio
- Internal Rate of Return (IRR)
- Subsidy Options
- Partnerships





Atlanta Regional MANAGED LANES Implementation Plan

Results of Financial Analysis





1) I-285 E Segment 1 & 2

I-285 E from I-20 E to I-85 N

Length	13.4 miles	Alternative	New Lanes		
Capital Costs (2018\$)	\$186 M	30-Yr Net Revenue (Gross revenue – O&M)	\$1,535 M		




Public Upfront Pmts (45% Upfront)	\$84
Total DBF Pmts (20 years)	\$230
Total Shortfall Payments*	\$3
Net Project Cashflow (Net Revenue – DBF Payments)	\$1,305
Net Cashflow / Capital	7.0



Public Upfront Pmts (45% Upfront)	\$84
Total DBF Pmts (10 Years)	\$162
Total Shortfall Payments*	\$16
Net Project Cashflow (Net Revenue - DBF Payments)	\$1,373
Net Cashflow / Capital	7.4




Public Upfront Pmts (70% Upfront)	\$130
Total DBF Pmts (10 years)	\$90
Total Shortfall Payments*	\$2
Net Project Cashflow (Net Revenue – DBF Payments)	\$1,445
Net Cashflow / Capital	7.8



30-Yr Gross Revenue	\$2,280
Net Project Cashflow	\$1,013
Debt Service	\$522
Net Upfront Proceeds (PV)	\$153
Net O&M	\$745
Financial Feasibility %	82%
(Proceeds / Capital Costs)	

Note: \$ are inflated to year of expenditure

*Total GDOT subsidy to cover years when annual toll revenue is insufficient to meet that year's DBF payment








5) I-75 S Segment 1

I-75 S from I-285 S to SR 138

Length	10.6 miles	Alternative	New Lanes
Capital Costs (2018\$)	\$354 M	30-Yr Net Revenue (Gross revenue – O&M)	\$277 M



Public Upfront Pmts (45% Upfront)	\$159
Total DBF Pmts (20 years)	\$439
Total Shortfall Payments*	\$330
Net Project Cashflow (Net Revenue - DBF Payments)	-\$161
Net Cashflow / Capital	-0.5




Public Upfront Pmts (45% Upfront)	\$159
Total DBF Pmts (10 Years)	\$309
Total Shortfall Payments*	\$289
Net Project Cashflow (Net Revenue - DBF Payments)	-\$32
Net Cashflow / Capital	-0.1



Public Upfront Pmts (70% Upfront)	\$248
Total DBF Pmts (10 years)	\$171
Total Shortfall Payments*	\$151
Net Project Cashflow (Net Revenue - DBF Payments)	\$107
Net Cashflow / Capital	0.3

Toll Revenue Analysis¹







Atlanta Regional

MANAGED LANES

Implementation Plan

Findings





Corridor Strategy Findings

				New Lanes Revenue and Costs for Each Segment (\$ in Millions, 2013)			Dynamic Flex Lanes Revenue and Costs for Each Segment (\$ in Millions, 2013)				
Corridor	Segment	Termini	Length (miles)	30-Year Gross Revenue	Capital Cost	30-Year O&M Cost	PFI	30-Year Gross Revenue	Capital Cost	30-Year O&M Cost	PFI
I-20 E	Segment 1	I-285 E to SR 124	9.8	\$730	\$268	\$239	1.8	\$695	\$80	\$225	5.9
I-20 W	Segment 1 & 2	I-285 W to SR 92	11.0	\$690	\$366	\$300	1.1	\$568	\$191	\$301	1.4
I-285 E	Segment 1 & 2	I-20 E to I-85 N	13.0	\$1,247	\$164	\$419	5.0	-	-	-	-
I-285 W	Segment 1 & 2	I-75 N to I-20 W	8.9	\$660	\$311	\$297	1.2	\$841	\$137	\$321	3.8
I-75 S	Segment 1	I-285 S to SR 138	11.0	\$338	\$313	\$194	0.5	-	-	-	-
I-85 N	Segment 1	I-285 N to Old Peachtree Rd	17.0	\$1,053	\$333	\$302	2.3	-	-	-	-
SR 316	Segment 1	I-85 to SR 120	6.5	\$256	\$151	\$172	0.6	\$333	\$148	\$182	1.0
SR 400	Segment 1 & 2	I-285 N to McFarland	17.0	\$1,236	\$497	\$412	1.7	-	-	-	-
	Т	otal	117.6	\$6,210	\$2,403	\$2,335	1.6	\$2,437	\$556	\$1,029	2.5




¹⁾ Total Capital cost includes roadway capital cost and tolling capital cost.

²⁾ Total 30-year O&M cost includes roadway O&M, tolling O&M and transaction cost.

³⁾ The Project Financebility Index (PFI) is calculated as: [30-year gross revenue] minus [30-year O&M costs for both roadway and toll equipment] divided by [roadway and tolling capital costs].



Corridor Strategy Findings







Next Steps

- Complete Documentation
- Atlanta MPO to consider corridor strategies as part of current RTP project prioritization process







Atlanta Regional

MANAGED LANES

Implementation Plan



www.dot.ga.gov\MLIP

Kyle Mote GDOT Office of Planning

(404) 631-1987

kmote@dot.ga.gov